

HONDA

EZ3000CX & EZ6500CXS - GENERAL FEATURES

- Design - Simple & strong design
- Handling - Excellent startability, Steady unit even with engine vibration, Easy access to engine oil filler cap, Two wheels and handles convenient for movement
- Reliability - Adopted highly reliable electromagnetic circuit protector
- Output - AVR system which helps to achieve stable voltage is adopted



	EZ3000CX	EZ6500CXS
AC Frequency	50Hz	
AC Output VOLTAGE	230V	
Rated AC output	2.2kVA	5kVA
Maximum AC output	2.5kVA	5.5kVA
Model	GP200	GX390
Engine Type	Air cooled 4 stroke OHV single cylinder	
Displacement	196cc	389cc
Ignition system	Transistorized magneto	
Starting system	Recoil	
Continuous operational time	8.3h	6.7h
Fuel tank capacity	13 Ltrs	15.5 Ltrs
Dimension (L*W*H)	595 x 435 x 485mm	684 x 533 x 538 mm
Dry weight	42.0 kg	80 kg
Noise level	66 dB(A)	72 dB(A)



Honda Mega Nairobi.
 38401 Uhuru Hwy., P.O. Box 9164- 00200
 Nairobi. Mobile: [0111222111](tel:0111222111)
hello@hondamega.com | www.hondamega.com